

FARMWORKS

SPRAY TANK FLUSH

Sprayer Tank Equipment Flush for Agriculture, Turf, and Horticulture Professionals

Optimize Performance of Spray Rigs for Agriculture and Vegetation Management

For Flushing All Working Parts:

- Tanks
- Hoses
- Nozzles
- Pumps
- Valves

FOR PROFESSIONAL USE ONLY

Keep Out of Reach of Children

INGREDIENT: Sodium Carbonate

NET WEIGHT: 2 LB / 32 OZ / 907.2 G

Directions on label are for rigs cleaned within reasonable time after use. If rig has been standing for a long period or is exceptionally dirty, additional time is required for FarmWorks® Spray Tank Flush to function.

When tanks are in extremely corroded condition, leakage may occur after using FarmWorks® Spray Tank Flush, due to removal of rust. FarmWorks® Spray Tank Flush does not attack steel, aluminum, brass, etc., but will remove rust which may be temporarily sealing the tank.

NOTICE: There are no warranties which extend beyond the description on the label hereof. The manufacturer, Ragan & Massey, Inc., warrants this product to be as described on the label. The manufacturer's liability on this warranty is limited to return of the purchase price of this product. The buyer assumes all risks and liability resulting from the use of this product, whether used singly or in combination with other goods. The manufacturer neither assumes nor authorizes any person to assume for it any other liability in connection with the sale or use of this product.

WARNING

Causes serious eye irritation. Wash hands thoroughly after handling. Wear eye protection. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. See Safety Data Sheet for additional information. EMERGENCY CONTACT: CHEMTREC (800) 424-9300

DISPOSAL

FarmWorks® Spray Tank Flush by itself does not have any disposal requirement but once used the solution must be disposed of according to the directions of the chemical from your spray rig at proper disposal area.

DIRECTIONS

1. Add ½ of the water needed based on the tank size;
2. Dissolve amount of FarmWorks® Spray Tank Flush needed to clean tank as shown by Use Rate chart;
3. Add remaining amount of water;
4. Close valve to spray boom;
5. Agitate vigorously;
6. Open bypass valve and circulate solution through spraying system for 15 minutes;
7. Use hose or hand sprayer to thoroughly wash all internal tank parts;

8. Open spray boom valve and allow solution to flow through entire spray boom as well as nozzles;
9. Refill tank with water to the same rate as previously used with FarmWorks® Spray Tank Flush to recirculate for 10 minutes and then flush through spray boom and nozzles. If changing chemicals, a second rinse is recommended with 25 gallons of water.

USE RATE

FarmWorks® Spray Tank Flush	Amount of Water	Tank Size
4 ounces	12.5 gallons	25 gallons
8 ounces	25 gallons	50 gallons
16 ounces	50 gallons	100 gallons
32 ounces	100 gallons	200 gallons

EXTRA PRECAUTIONS SHOULD BE FOLLOWED AFTER USING 2,4-D OR SIMILAR MATERIALS.

Hoses, rubber connections, pump and hand gun packing are more likely to retain 2,4-D than tank, boom or metal parts, equal attention should be given to the flushing of these. Many authorities recommend renewal of soft parts after using 2,4-D. However, if these are in good condition, FarmWorks® Spray Tank Flush will clean them.

1. Flush complete rig with plain water, inside and out;
2. Use as directed on label except allow FarmWorks® Spray Tank Flush to remain in rig and hoses overnight;
3. Take liberal sample of second rinse from each section of boom and hand gun;
4. Sprinkle these samples on particularly susceptible plants such as tomato, cotton, etc. to determine if cleaning was sufficient. Period required to show 2,4-D varies with temperature and humidity. 48 hours is usually enough.
5. If tests show 2,4-D present replace hoses, pump packing, rubber connections, etc. and repeat entire process including test.

Distributed by:

Ragan & Massey, Inc.

101 Ponchatoula Parkway, Ponchatoula, LA 70454

(800) 264-5281

info@raganandmassey.com



7 37716 75310 3